



Technical Datasheet of Flexible Cables				LDIS09CYUAY1005C006S
Sr.No.	Description	Unit	5C X 6	
			Sq. mm.	
1	Manufacturer Name		Polycab Wires Private Limited	
2	Brand Name		POLYCAB	
3	Rated Voltage		1100V	
4	CONDUCTOR			
	a) Material		Plain annealed high conductivity Flexible copper conductor as per Class 5 of IS 8130/2013 latest	
	b) Conductor Size	Sq.mm	6	
	c) Max. D.C Cond. Resistance at 20 Deg. C.	Ohm/km	3.3	
5	INSULATION			
	a) Material		PVC Type 'D'	
	b) Nominal Thickness in mm.	mm	0.8	
	c) Core Identification		Red, Yellow, Blue, Black & Grey	
6	Sheath			
	Material		PVC Type 'ST3' as per IS:5831/84	
	Nominal Thickness in mm.		1.40	
	Sheath Colour		Black	
7	Maximum Overall Diameter	mm	Approx-16.1 ± 2.0	
8	Current rating	Amps	37	
9	Max. conductor temp. under normal operating conditions	°C	70°C	
10	Max conductor temp at the termination of short circuit	°C	160°C	
11	Standards to which the cables confirm		As per IS 8130/2013, IS 694/2010, etc. with latest up to date amendments	
12	Recommended minimum bending radius in mm		8 times the overall diameter of the cable	
13	Max. Tensile strength when pulled with pulling eye	Kg	153	
14	Printing		POLYCAB 1100 V, NO.OF CORE X SQ.MM	